

Information Sheet Of Loading Port Facilities

Country	:	Indonesia
Name of Port	:	Balickpapan Coal Terminal
Location	:	Teluk Tebang, Tanjung Batu - Kelurahan Kariangau Balickpapan
Name of Berth	:	BCT Export Jetty
Berth :		
(1) Depth (m)	:	17 - 19 M
(2) Length (m)	:	315 M with extra dolphins
Channel Depth (m)	:	-13 M LWS, Max Tide = 2.7 M
Maximum Permissible Vessel Limit :		
(1) L.O.A (m)	:	Upto 300 M
(2) Beam (m)	:	Upto 42 M
(3) D.W.T (mt)	:	Upto 160.000 MT
(4) Draft (m)	:	(13m + tide) - 10% ukc
Ship Loader(s) :		
(1) No of Loaders	:	2 Loaders
(2) Capacity (TPH)	:	Max - 8.000 TPH/hr, average - 7.000 TPH/hr
(3) Outreach (m)	:	Approx - 20 M
(4) Clean Height (m)	:	Approx - 17 M
(5) Travel Distance (m)	:	180 M
Operation Data :		
(1) Operators	:	3 persons per shift / day
(2) Working Hours	:	Day shift (08:00-20:00), Night shift (20:00-08:00)
(3) Annual Throughput	:	15.000.000 MT
Stockpile Capacity (mt)	:	± 1.000.000 MT
Guaranteed Loading Rate (mt/wwd)	:	<ul style="list-style-type: none"> • Handymax 25.000 mt / wwd • Panamax 30.000 mt / wwd
Safe Berth & Safe Port Guarantee	:	<input checked="" type="checkbox"/> Yes (Safe Berth & Safe Port)
Permissible Vessel Type	:	<input type="checkbox"/> Only Geared Type <input type="checkbox"/> Only Gearless Type <input checked="" type="checkbox"/> Either Geared or Gearless Type
Other Special Requirements for Vessel to Load	:	<ul style="list-style-type: none"> - Max air-draft : 17 M - Vessel deballasting rate : min 2.000 mt/hrs